

Hangzhou Sanyuan Cable Co.,Ltd

RG type coaxial cable (UL Style 1354)

Standard:U.S.A.MIL-C-ITD

Model	Inner conductor Number/outer diameter(mm)	Outer diameter of dielectric(mm)	Al foil	Braiding Wire Shield n/(mm)	Outer diameter of sheath(mm)	Characteristic impedance (Ω)
RG-5/U	1/1.29	4.7±0.20	17*0.04	32/48/64/80/96/112/0.12 BC/AL/TC	8.4±0.20	51.5
RG-6/U	1/1.0	4.8±0.20	17x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	7.0±0.20	75.0
RG-6/U	1/1.02	4.7±0.20	17x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	8.4±0.20	76.0
RG-6/UR	7/0.5	4.8±0.20	17x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	7.0±0.20	50.0
RG-6A/U	1/0.724	4.7±0.20	17x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	8.4±0.20	75.0
RG-7/U	1/0.914	7.0±0.20	25x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	9.4±0.20	75.0
RG-8/U	7/0.724	7.2±0.20	25x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	10.3±0.20	50.0
RG-10/U	7/0.724	7.2±0.20	25x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	12.0±0.20	52.0
RG-11/U	7/0.4	7.2±0.20	25x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	10.3±0.20	75.0
RG-12/U	7/0.4	7.2±0.20	25x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	12.0±0.20	75.0
RG-13/U	7/0.4	7.1±0.20	25x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	10.6±0.20	74.0
RG-14/U	1/2.59	9.9±0.20	34 x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	13.8±0.20	52.0
RG-21/U	1/1.29	4.7±0.20	17 x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	8.43±0.20	53.0
RG-22/U	7/0.39	7.2±0.20	25 x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	10.2±0.20	95.0
RG-29/U	1/0.813	2.9±0.20	11x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	4.7±0.20	53.5
RG-54A/U	7/0.386	4.5±0.20	17x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	6.1±0.20	58.0
RG-55/U	1/0.81	2.9±0.20	11x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	5.2±0.20	53.5
RG-56/U	1/0.813	2.9±0.20	11x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	6.0±0.20	53.5
RG-58/U	1/0.813	2.9±0.20	11x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	4.95±0.20	75.0
RG-58/UR	19/0.18	3.0±0.20	11x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	5.00±0.20	75.0
RG-59/U	1/0.643	3.7±0.20	13x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	6.15±0.20	75.0
RG-59/U	19/0.15	3.7±0.20	13x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	6.15±0.20	75.0
RG-59A/U	1/0.64	3.7±0.20	13x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	6.15±0.20	73.0
RG-59B/U	1/0.58	3.7±0.20	13x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	6.15±0.20	93.0
RG-62/U	1/0.643	3.7±0.20	13x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	6.15±0.20	93.0
RG-63/U	1/0.64	7.2±0.20	25x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	10.29±0.20	125.0
RG-71/U	1/0.64	3.7±0.20	13x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	6.4±0.20	93.0
RG-83/U	1/2.58	6.1±0.20	25x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	10.4±0.20	35.0
RG-122/U	27/0.127	3.4±0.20	13x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	4.1±0.20	50.0
RG-133A/U	1/0.645	7.2±0.20	25x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	10.3±0.20	85.0
RG-141A/U	1/0.99	2.9±0.20	11x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	4.83±0.20	50.0
RG-142B/U	1/0.99	2.9±0.20	11x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	4.95±0.20	50.0
RG-174A/U	7/0.16	1.5±0.20	7x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	2.54±0.20	50.0
RG-188A/U	7/0.17	1.5±0.20	7x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	2.79±0.20	50.0
RG-213U	7/0.724	7.2±0.20	25x0.04	32/48/64/80/96/112/0.12 BC/AL/TC	10.3±0.20	50.0

Hangzhou Sanyuan Cable Co.,Ltd

RG-214/U	7/0.75	7.2±0.20	25×0.04	32/48/64/80/96/112/0.12 BC/AL/TC	10.8±0.20	50.0
RG-216U	1/0.40	7.2±0.20	25×0.04	32/48/64/80/96/112/0.12 BC/AL/TC	10.8±0.20	75.0
RG-217U	1/2.69	9.4±0.20	30×0.04	32/48/64/80/96/112/0.12 BC/AL/TC	13.8±0.20	50.0
RG-233/U	1/0.89	2.9±0.20	11×0.04	32/48/64/80/96/112/0.12 BC/AL/TC	5.49±0.20	50.0
RG-303/U	1/0.99	2.9±0.20	11×0.04	32/48/64/80/96/112/0.12 BC/AL/TC	4.32±0.20	50.0
RG-316/U	7/0.17	1.5±0.20	7×0.04	32/48/64/80/96/112/0.12 BC/AL/TC	2.59±0.20	50.0
RG-400/U	7/0.2	2.9±0.20	11×0.04	32/48/64/80/96/112/0.12 BC/AL/TC	4.45±0.20	50.0